
BOS-G





- **Convenient**

Quick installation standard of 19-inch embedded designed module is comfortable for installation and maintenance.

- **Safe and reliable**

Cathode material is made from LiFePO4 with safety performance and long cycle life, The module has less self-discharge, up to 6 months without charging it on shelf, no memory effect, excellent performance of shallow charge and discharge.

- **Intelligent BMS**

It has protection functions including over-discharge, over-charge, over-current and over-high or low temperature. The system can automatically manage charge and discharge state and balance current and voltage of each cell.

- **Eco-friendly**

The whole module is non-toxic, non-polluting and environmentally friendly.

- **Flexible configuration**

Multiple battery modules can be in parallel for expanding capacity and power. Support USB upgrade, wifi upgrade(optional), remote up grade(Compatible with Deye inverter).

- **Wide temperature**

Working temperature range is from -20°C to 55°C, with excellent discharge performance and cycle life.

Deye

Technical Data

Model	BOS-G		
Main Parameter			
Cell Chemistry	LiFePO4		
Module Energy(kWh)	5.12		
Module Nominal Voltage (V)	51.2		
Module Capacity(Ah)	100		
Battery Module Qty in series. (Optional)	3 (Min)	8 (Standard US Cluster)	12 (Standard EU Cluster)
System Nominal Voltage (V)	153.6	409.6	614.4
System Operating Voltage (V)	124.8~175.2	332.8~467.2	499.2~700
System Energy (kWh)	15.36	40.96	61.44
System Usable Energy (kWh) [1]	13.8	36.86	55.29
Charge/Discharge Current (A) [2] — Recommend	50		
Charge/Discharge Current (A) [2] — Nominal	100		
Charge/Discharge Current (A) [2] — Peak Discharge (2 mins, 25°C)	125		
Working Temperature(°C)	Charge: 0~55/Discharge: -20~55		
Status Indicator	Yellow: Battery High Voltage Power On Red: Battery System Alarm		
Communication Port	CAN2.0/RS485		
Humidity	5~85%RH		
Altitude	≤2000m		
IP Rating of Enclosure	IP20		
Dimension (W/D/H,mm)	589*590*1640		589*590*2240
Weight Approximate (kg)	258	434	628
Installation Location	Rack Mounting		
Storage Temperature(°C)	0~35		
Recommend Depth of Discharge	90%		
Cycle Life	25±2°C, 0.5C/0.5C, EOL70%≥6000		
Warranty [3]	10 years		
Certification	CE/IEC62619 / UL1973 / UL9540A / UN38.3		

1 DC Usable Energy, test conditions: 90% DOD, 0.2C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.

2 The current is affected by temperature and SOC.


3 The warranty is due whichever reached first of warranty period or life cycle power.

Deye
NINGBO DEYE ESS TECHNOLOGY CO., LTD
NO. 18TH ZHENGLONG ROAD LONGHSAN CIXI NINGBO ZHEJAING 315311 P.R.CHINA
Tel: +86-0574-8622 9263 | E-mail: sales@deye.com.cn

System Components


Model	Description
HVB750V/100A-EU	High Voltage Battery cluster control box conforming to European or British Standards

Operating Voltage	120 ~ 750Vdc
Nominal Charge/Discharge Current	100A
Max.Charge/Discharge Current	125A
DC Input Rating	12±2%V/4.15A
Operating Temperature Range	-20~65°C
Ingress Protection	IP20
Dimension (W/D/H)	440*570*150mm
Weight Approximate	15.5kg



HVB750V/100A-US	High Voltage Battery cluster control box conforming to North American Standard

Operating Voltage	120 ~ 750Vdc
Nominal Charge/Discharge Current	100A
Max.Charge/Discharge Current	125A
DC Input Rating	12±2%V/4.15A
Operating Temperature Range	-20~65°C
Ingress Protection	IP20
Dimension (W/D/H)	440*570*150mm
Weight Approximate	17kg




High voltage box Standard configuration:
① 120 ohm terminal resistance
② 140mm communication cable
③ 220mm power cable
④1.5m power cable（US Version）
2.1m power cable（EU Version）
⑤Power plug



BOS-GM5.1	5.12 kwh battery module

Battery Type	LiFePO4(LFP)
Nominal Voltage	51.2Vdc
Rated Capacity	100Ah
Rated Energy	5.12kWh
Nominal Charge/Discharge Current	100A
Peak.Discharge Current	125A
Charge Temperature	0~55°C
Discharge Temperature	-20℃ ~ 55°C
Storage Temperature	0℃ ~ 35°C
Ingress Protection	IP20
Dimension (W/D/H)	440*570*133mm
Weight Approximate	44kg



Battery module Standard configuration:
①110mm communication cable
② 200mm power cable



EPCable5.0(Optional)	Standard 5-meter power cable connected to the positive pole of the external PCS

1000V/4AWG cable



ENCable5.0(Optional)	Standard 5-meter power cable connected to the negative pole of the external PCS

1000V/4AWG cable



System Components


Model	Description
EPWR Cable5.0(Optional)	Standard 5-meter cable connected to external 12VDC power supply




ECOM Cable5.0(Optional)	Standard 5-meter commumication cable connected to the external device



3U-HRACK(Optional)	Standard 19inch rack, caninstall 12 pcs batteries and 1 pcs High Voltage Battery cluster control box
Dimension (W/D/H)	589*590*2240mm
Weight Approximate	85kg



3U-LRACK(Optional)	Standard 19inch rack, caninstall 8 pcs batteries and 1 pcs High Voltage Battery cluster control box
Dimension (W/D/H)	589*590*1640mm
Weight Approximate	65kg



NINGBO DEYE ESS TECHNOLOGY CO., LTD
NO. 18TH ZHENGLONG ROAD LONGHSAN CIXI NINGBO ZHEJAING 315311 P.R.CHINA
Tel: +86-0574-8622 9263 | E-mail: sales@deye.com.cn