Wireless Gateway and Repeater

For Europe & APAC


COMMUNICATION



5 YEAR WARRANTY

Simple Wireless Connectivity

- Wirelessly connects SetApp-enabled SolarEdge inverters to an Internet router
- Easy installation and configuration via SetApp, leveraging a Wireless station built into the inverter
- Antenna* is located external to the inverter and supports up to two repeaters for extended range
- The Wireless Gateway supports up to eight SolarEdge inverters on a single wireless network



* Two Wi-Fi antennas are included in the supplied kit, one that connects to the inverter and the other to the Wireless Gateway. There is no need to order them separately.

solaredge.com

solaredge

/ Wireless Gateway and Repeater

For Europe & APAC

PART NUMBER	SE-WFGW-B-S1-RW, SE-WFRPT-B-S1-RW	UNITS
MODEL NUMBER	WiFi-GW	
COMPATIBLE INVERTERS	RESIDENTIAL INVERTERS WITH SETAPP CONFIGURATION	
RF PERFORMANCE		
Transmit Power	15	dBm
Receiver Sensitivity (802.11b @ 1Mbps DSS)	-94 to -69	dBm
EIRP with Antenna	20	dBm
Outdoor (LOS) Range	400 / 1300	m / ft
Indoor Range (1)	50 / 160	m / ft
Frequency Band	2412 - 2472	MHz
Bandwidth	20	MHz
Antenna Gain(2)	5	dBi
NETWORK AND SECURITY		
Channels(3)	1-13	
Security	WPA-PSK, WPA2-PSK, WEP	
WIRELESS LAN		
Standards	802.11b/g/n	
Modulation	802.11b - DSSS-CCK, 802.11g - OFDM, 802.11n - HT modulations, MCS0-7	
Data Rates	1 - 72	Mbps
ENVIRONMENTAL		
Operating Temperature	-20 to +60 / -4 to +140	°C / °F
Storage Temperature	-20 to +60 / -4 to +140	°C / °F
Relative Humidity (non-condensing)	0 - 80	%
Ingress Protection	IP20	
MECHANICAL		
Dimensions (H x W x D; with pins)	66.3 x 48 x 82.7 / 2.6 x 1.8 x 3.2	mm / in
Weight without Antenna	90 / 0.20	gr / lb
Weight with Antenna	110 / 0.24	gr / lb
POWER SUPPLY		
AC Voltage (nominal)	100 - 240	Vac
AC Frequency (nominal)	50 / 60	Hz
Max Input Current	50	mA
STANDARD COMPLIANCE		
Safety	IEC/ EN 62368-1	
EMC	EN301 489-1; EN301 489-17; EN300 328; EN55032:2015+AC:2016; EN55035; EN61000- 3-2:2041; EN61000-3-3:2013; EN61000-4-2:2009; EN61000-4-3:2006+A1:2008+A2:2010; EN61000-4-4:2012; EN61000-4-5:2014+A1:20174; EN61000-4- 6:2014+AC:2015; EN61000-4-11:2004+A1:2017; AS/NZS 4268:2017	
AC Plug	EN 50075	


(1) Approximate values, may differ depending on specific installation conditions
(2) The antenna may have higher gain within EIRP power constraint
(3) Channels 12-13 are allocated for future use

Wireless Gateway and Repeater

For Europe & APAC


Scenario A: Single inverter, wireless connection with optional repeaters

- 1 x Wireless gateway
- 1 or 2 x Wireless repeater for extending the Wi-Fi range




Scenario B: Multiple inverters, wired connection(4)

- 1 x Wireless gateway



Scenario C: Multiple inverters, Wi-Fi Point to Multi-point(5)

- 1 x Wireless gateway



(4) To extend the Wi-Fi range, add one or two Wireless repeaters
(5) Additional inverter antennas should be purchased separately

CE

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREDGE, the SolarEdge logo, OPTIMIZED BY SOLAREDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: 07/2021 DS-000062-1.2-ENG. Subject to change without notice.

solaredge